

EU-TYPE EXAMINATION CERTIFICATE



The following model of Personal Protective Equipment has been subjected to an EU-type examination in accordance with the module B of the PPE regulation (2016/425) and has been shown to satisfy to essential health and safety requirements.

Certificate N° 0075/797/162/03/19/0976 - EXT 02/03/19

Issued by CTC, Notified Body N°0075, to the following model of personal protective equipment:

Manufacturer: HONEYWELL SAFETY PRODUCTS EUROPE

Immeuble Edison ZI-Paris Nord II 33, Rue des Vanesses 95 958

France

Description

PPE Type: protective glove against mechanical risks, chemical risks,

microorganisms risks

Product reference: 860FWG

Glove description: Glove dark green 100% PVC with liner of 100% cotton jersey. Coating has

non slip surface on hand portion.

Available sizes: 8 M 9 L 10XL

Pictures:







Address

HONEYWELL SAFETY PRODUCTS EUROPE Immeuble Edison ZI-Paris Nord II 33 Rue des Vanesses 95 958 ROISSY CDG CEDEX France

Address has to be printed on back side of the gloves or on a label inside the

Reference standard:

Levels of performance / class of protection

EN 420:2003+A1:2009

EN 388:2016

4121X

« X »indicates that the glove has not been submitted to the test or the test method appears not to be suitable for the glove design or material.

EN ISO 374-5:2016

MICRO-ORGANISMS

EN ISO 374-1:2016

Type B KLNOT

re with the center

This product is a category III (letal or irreversible risk). This certificate shall only be used in conjuncture with the conformity assessment procedure according to module C2 (CTC 0075)

At the date of certificate the product is in compliance with Annex XVII of REACh regulation (n° 1907/2006 and revisions)

Full description of the PPE, reference rules verified in the context of the EU-type examination and information given on the product are detailed in the manufacturer's technical file index 01 dated from March 2019

NOTA: Any modification to new items of the personal protective equipment object of this EU type approval certificate or any modification of the information contained in the manufacturer technical file which served for the deliverance of the EU type approval certificate (change of address, change of company status) should be brought to the attention of the notified body in accordance with Annex V §7.2 of Regulation 2016/425.

Issued in Lyon by
Lionel GAUDILLERE
PPE Certification Manager



Date of first issue: 25 March 2019 End of validity date: 25 March 2024





Original CTC

In application of the Regulation 2016/425 of the European parliament and the Council of 9th March 2016 related to Personal Protective Equipment and repealing the Directive 89/686/FEC.

www.ctcgroupe.com

cemarking@ctcgroupe.com

HONEYWELL SAFETY PRODUCTS EUROPE

MANUFACTURER'S TECHNICAL FILE TO THE PPE REGULATION 2016/425

Reference of the product : 860FWG

Article code :

Technical file index : 01

Last update : March 2019

IDENTIFICATION

Reference of the product: : 860FWG

Article code:

Major Variant 850FWG

Technical file index: : 01

Last update: : March 2019

Manufacturer:

HONEYWELL SAFETY PRODUCTS EUROPE

Immeuble Edison ZI-Paris Nord II 33, Rue des Vanesses 95 958 ROISSY CDG CEDEX

France

tel: 01.49.90.79.79 fax: 01.49.90.79.80

Factory:

Prime Safety Limited

Block 6, Dr. Mehmood Hussain Road 75400 Karachi

Pakistan

tel: 14 164 479 040 fax: 14 164 478 694

IHPL Bangladesh

Industrial Hand Protection Ltd, Plot 6 Sector 1A, CHITTAGONG BANGLADESH

tel: Phone No: 0088-031-740781-2 fax: Fax No: 0088-031-740784

GLOVE DESCRIPTION

General glove description:

Glove dark green 100% PVC with liner of 100% cotton jersey. Coating has non slip surface on hand portion.

type of coating finish: no coating

Visual description (picture back and palm sides):



Field of use

mechanical, high chemical,

Agriculture, Automotive and Part Manufacturer, Chemical Industries, Petro-chemical, Water treatment

	Risk assessment (Essential Health and Safety Requirement. Annex II - PPE Regulation)				
		Applicable	Covered by		
§1	Requirements defined in the Annex II §1 are applicable to all PPE	Ŋ	Standard Instruction for use Marking		
§1.4	Manufacturer's instructions and information is available	V	Standard Instruction for use Marking		
§2.5	PPE which may be caught up during use	V	Standard Instruction for use Marking		
§2.12	PPE bearing one or more identification markings or indicators directly or indirectly relating to health and safety	V	✓ Standard ✓ Instruction for use ✓ Marking		
§2.14	Multi-risk PPE	V	✓ Standard ✓ Instruction for use ✓ Marking		
§3.3	The PPE is intended to protect against mechanical injuries	V	✓ Standard ✓ Instruction for use ✓ Marking		
§3.10.2	PPE intended to protect against substances and mixtures which are hazardous to health and against harmful biological agents - Cutaneous contact	V	✓ Standard ✓ Instruction for use ✓ Marking		

Available sizes:

Minimum length of glove (mm) Minimum width of glove (mm)	Sizes
400 /112,5	8 M
400 /122,5	9 L
400 /126	10XL

Glove constitution:

	Reference	Color	Material	Surfacic mass	Gauges	Thickness
Palm	2930004	Dark green	PVC			1.6 - 1.8 mm
Tulli	2932001	Natural	Silice powder			
Back	2930004	Dark green	PVC			1.6 - 1.8 mm
Dack	2932001	Natural	Silice powder			
Lining	2923008	Natural	Cotton jersey	220 gr/m²		
Cuff	2930004	Dark green	PVC			1.3 - 1.6 mm

PROTECTION SCOPE

This glove meets the essential requirements of the Personal Protective Equipment Regulation 2016/425.

This glove is designed for against mechanical risks, chemical risks, microorganisms risks.

It is a category III product, module C2

Notified Body Reference: CTC (0075)

4, rue Hermann Frenkel 69367 LYON

GENERAL REQUIREMENTS

Standard EN 420 : 2003 + A1 : 2009

Dexterity: 4

Size: conform

At the date of certificate the product is in compliance with Annex XVII of REACh regulation (n° 1907/2006 and revisions)

SPECIFIC REQUIREMENTS AND PERFORMANCE LEVELS

Mechanical hazard EN 388: 2016

Protection offered	Performance levels
Abrasion resistance	4
Blade cut resistance	1
Tear strength resistance	2
Puncture resistance	1
Cut Resistance method (EN ISO 13997)	X
Impact Protection	-

The levels of performance have been measured on the palm

Chemical hazard EN 374-2: 2014

Protection offered	Performance levels
Water tighness	conform
Air tighness	conform

Chemical hazard EN ISO 374-1: 2016

Type :	Type B

Tested chemical:	CAS N°	Letter	Permeation performance levels:	Degradation value:
Sodium hydroxide 40%	1310-73-2	K	6	-16,3%
Sulphuric acid 96%	7664-93-9	L	4	-30,2%
Acetic acid 99%	64-19-7	N	3	-41,7%
Ammonium hydroxide 25%	1336-21-6	0	6	-33,0%
Formaldehyde 37%	50-00-0	Т	6	-27,0%

Microorganism EN ISO 374-5: 2016

This glove protect against microorganism Uncontrolled against viruses

[«] X » indicates that the glove has not been submitted to the test or the test method appears not to be suitable for the glove design or material.

TEST REPORTS

Laboratory	CTC	Other
EN 420 + innocuousness	L150404268_1 1210-14429/1 1305-8534/1	
EN 388	L150404266_1 L170815790_1 L180203049_1	
EN 374-2	L150404266_1	
EN 16523-1	L160712922_1 L160609557_1 L150404308_1 L161120040_1 L181020436_1 L181020435_1	
Other	L150404268_1 L161017737_1	

MARKING - PACKAGING

Information printed on the glove:

Logo of Manufacturer:

Logo (€

Glove's reference: 860FWG

Article Code : Size indicator


Pictograms related to risks against which protection is offered with performance levels

Information pictogram

Address of Manufacturer:

Date of Manufacture (month/year) and/or Serial number :

Marking example:





Method of marking on the glove :

Tampography

Packaging:

12 pairs per bag, 6 bags per box

PPE subject to ageing :

The design performance can not be significantly affect by ageing when stored in appropriate conditions (humidity, temperature, clean, ventilated, light).

Declaration of conformity:

Available on : https://doc.honeywellsafety.com/

MEANS OF CONTROL

Final Inspection : in accordance to ISO 2859 level 2. Major defects : NQA = 0,65 / Minor defects : NQA = 0,65.

Sampli	ng Plan	Quantity of acceptable defects		
Lot Quantity	Sample Quantity	Minor Defects	Major Defects	
110 to 200	D 8	2	0	
201 to 500	F 20	5	1	
501 to 1200	G 30	7	1	
1201 to 10000	J 80	14	3	
10000	K 125	21	5	